

# Compass<sup>®</sup> 360

## TOUCHSCREEN

### 12.1" TOUCH SCREEN

Responsive single pane capacitive touch screen.

### ONE-PIECE GLASS FACE

### HIDDEN SPEAKER

### ACCESSIBILITY BUTTON

### OPTIONAL CARD READER WITH LIGHTED LOGO



White

Black

Silver

Gold



AVAILABLE IN  
ANGLE OR FLUSH  
MOUNTED DESIGNS.

SELECT FROM 4 COLOR  
COMBINATIONS.

# OTIS

Learn more at [otis.com](https://www.otis.com)

© 2020 OTIS ELEVATOR COMPANY.

# Compass<sup>®</sup> 360

## TOUCHSCREEN – TECHNICAL SPECIFICATIONS

TOUCHSCREEN		
MOUNTING OPTIONS	ANGLED	FLUSH
Dimensions H x W x D	287 x 304 x 63mm (11.3 x 12.0 x 2.5in)	377.9 x 320.9 x 76.9mm (14.9 x 12.6 x 3.0in)
Energy Consumption Optional RFID reader adds 0.6W to max	270mA @ 48VDC (13W)	
Screen	12-inch Capacitive Touch Screen with 1024 x 768 dpi resolution	
Standby	Yes, after a selectable period of non-operation	
Temperature Range	Temperature: 0-40 degrees C (32-104 degrees F)	

### CARD READER INFORMATION

Optional multiple integrated reader technologies available.  
Talk to your Otis Elevator Representative for more information on available reader types and capabilities.

Types of Card Readers	RFID: Elatec TWN4 MultiTech 2 PI <sup>1</sup>
	RFID/Mobile capability, DirectKey (Blue Diamond App); HID RFID and HID Mobile App.
Supported Frequencies	125kHz/134kHz, 13.56MHz, 2.4-2.48GHz
Protocols	ISO14443A, ISO14443B, ISO18092, ISO15693

1. Default selection 2. Optional selection

### COMPLIANCE

Elevator Safety Code Compliance	North America: ASME A17.1-2016/ CSA B44-16
	Other Regions: EN81-20 , EN-81-50
Accessibility Code Compliance	North America: A117.1–2017
	Other Regions: EN81-70:2018
EU Reach Compliance	Article 33

### CALIFORNIA COMPLIANCE

